

Unit 144, Riverdale, MD 20737-1236; (301) 734-5255.

SUPPLEMENTARY INFORMATION: The Animal and Plant Health Inspection Service's (APHIS) Plant Protection and Quarantine program (PPQ) provides certification of plants and plant products as a service to exporters. After assessing the phytosanitary condition of the plants or plant products intended for export, relative to the receiving country's regulations, an inspector issues an internationally recognized phytosanitary certificate (PPQ Form 577), a phytosanitary certificate for reexport (PPQ Form 579), an export certificate for processed plant products (PPQ Form 578), or a certificate of heat treatment (PPQ Form 553) if warranted. The regulations concerning export certification for plants and plant products are contained in 7 CFR part 353. Currently, more than 1,000 phytosanitary certificates are being tracked and issued manually per year.

Since 2002, PPQ has been working with Electronic Data Systems to develop a national Phytosanitary Certificate Issuance and Tracking System (PCIT), which would improve the tracking and traceback of Federal phytosanitary certificates, improve reporting capabilities, and reduce the incidence of errors and fraud. The PCIT is an interactive, Web-based system that will allow U.S. exporters to apply for phytosanitary certificates, schedule commodity inspections, and make payments on-line. PCIT will also allow APHIS to better manage Authorized Certification Officers' workload and enhance security and accountability of phytosanitary certificates.

In order to demonstrate the capabilities of the system and to provide information to interested industries about PCIT releases 2.0, 2.5 (the payment engine), and 3.0, PPQ will be holding a public meeting on July 14, 2005, in Riverdale, MD.

Registration

Due to space considerations, attendance at the public meeting will be limited to 100 people. We encourage preregistration. You may register by visiting <http://www.aphis.usda.gov/ppq/pim/exports/pcit/> or by contacting Ms. Linda Toran by July 8, 2005, at (301) 734-5307 or by fax at (301) 734-8693. Onsite registration for any remaining spaces will be held on the day of the meeting from 8 a.m. to 9 a.m.

Parking and Security Procedures

Please note that a fee of \$2.25 is required to enter the parking lot at the USDA Center at Riverside. The machine accepts \$1 bills or quarters.

Picture identification is required to be admitted into the building. Upon entering the building, visitors should inform security personnel that they are attending the PCIT meeting.

Done in Washington, DC, this 15th day of June, 2005.

Elizabeth E. Gaston,

Acting Administrator, Animal and Plant Health Inspection Service.

[FR Doc. E5-3205 Filed 6-20-05; 8:45 am]

BILLING CODE 3410-34-P

DEPARTMENT OF AGRICULTURE

Forest Service

Notice of Resource Advisory Committee Meeting

AGENCY: Modoc Resource Advisory Committee, Alturas, California, USDA Forest Service.

ACTION: Notice of meeting.

SUMMARY: Pursuant to the authorities in the Federal Advisory Committees Act (Public Law 92-463) and under the Secure Rural Schools and Community Self-Determination Act of 2000 (Pub. L. 106-393) the Modoc National Forest's Modoc Resource Advisory Committee will meet Monday, July 11th, 2005, August 1st, 2005 and August 29th, 2005 in Alturas, California for business meetings. The meetings are open to the public.

SUPPLEMENTARY INFORMATION: The business meeting July 11th begins at 6 pm., at the Modoc National Forest Office, Conference Room, 800 West 12th St., Alturas. Agenda topics will include existing and future projects that meet the intent of Pub. L. 106-393. Time will also be set aside for public comments at the beginning of the meeting.

The business meeting August 1st begins at 6 pm; at the Modoc National Forest Office, Conference Room, 800 West 12th St., Alturas. Agenda topics will include existing and future projects that meet the intent of Pub. L. 106-393. Time will also be set aside for public comments at the beginning of the meeting.

The business meeting August 29th begins at 6 pm; at the Modoc National Forest Office, Conference Room, 800 West 12th St., Alturas. Agenda topics will include existing and future projects that meet the intent of Pub. L. 106-393. Time will also be set aside for public comments at the beginning of the meeting.

FOR FURTHER INFORMATION CONTACT: Stan Sylva, Forest Supervisor and Designated Federal Officer, at (530) 233-8700; or

Public Affairs Officer Louis J Haynes at (530) 233-8846.

Stanley G. Sylva,

Forest Supervisor.

[FR Doc. 05-12188 Filed 6-20-05; 8:45 am]

BILLING CODE 3410-11-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-588-824]

Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Preliminary Results of Antidumping Duty Changed Circumstances Review and Intent Not to Revoke, In Part

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

SUMMARY: On December 7, 2004, the Department of Commerce ("the Department") published a notice of initiation of a changed circumstances review regarding certain corrosion-resistant carbon steel flat products from Japan in response to a request for partial revocation received from Metal One Corporation ("Metal One"), and invited interested parties to submit comments. On December 27, 2004, United States Steel Corporation ("U.S. Steel") submitted a letter opposing the request for revocation. As a result, we preliminarily determine not to revoke the order, in part, with respect to the diffusion-annealed nickel plate products covered by Metal One's request.

EFFECTIVE DATE: June 21, 2005.

FOR FURTHER INFORMATION CONTACT:

Christopher Hargett, AD/CVD Operations, Office 3, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW, Washington, DC 20230; telephone (202) 482-4161.

SUPPLEMENTARY INFORMATION:

Background

On October 13, 2004, Metal One filed a request for a changed circumstances review on diffusion-annealed nickel plate, in accordance with 19 CFR 351.216(b). Metal One argued that its products were similar to products already excluded from the order. *See Letter from Metal One*, October 13, 2004. On December 7, 2004, the Department published in the **Federal Register** a notice of initiation of a changed circumstances review on certain corrosion-resistant carbon steel flat products from Japan with respect to

diffusion-annealed nickel plate. *See Notice of Initiation of Antidumping Duty Changed Circumstances Review*, 69 FR 70633 (December 7, 2004). On December 27, 2004, U.S. Steel submitted comments on the Department's initiation of a changed circumstances review. Specifically, U.S. Steel asserted that the domestic producers maintain interest in the products included in the changed circumstances review. U.S. Steel stated that their production of the domestic like product is will in excess of 15 percent of total domestic production. *See Letter from U.S. Steel*, December 27, 2004. Furthermore, U.S. Steel claimed that the products Metal One requested be excluded from the order are significantly different from those excluded by the Department in July 2002, and fall within the scope of the order. *See Letter from U.S. Steel*, December 27, 2004. On December 29, 2004, two days after the close of the comment period for the initiation period, Thomas Steel Strip Corporation ("Thomas Steel") submitted comments objecting to the changed circumstances review. Because the letter was untimely filed, the Department has not taken the comments from Thomas Steel into consideration.

Scope of Order

The products subject to this order include flat-rolled carbon steel products, of rectangular shape, either clad, plated, or coated with corrosion-resistant metals such as zinc, aluminum, or zinc-, aluminum-, nickel- or iron-based alloys, whether or not corrugated or painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating, in coils (whether or not in successively superimposed layers) and of a width of 0.5 inch or greater, or in straight lengths which, if of a thickness less than 4.75 mm, are of a width of 0.5 inch or greater and which measures at least 10 times the thickness, or if of a thickness of 4.75 mm or more, are of a width which exceeds 150 mm and measures at least twice the thickness, as currently classifiable in the HTS under item numbers: 7210.30.0030, 7210.30.0060, 7210.41.0000, 7210.49.0030, 7210.49.0090, 7210.61.0000, 7210.69.0000, 7210.70.6030, 7210.70.6060, 7210.70.6090, 7210.90.1000, 7210.90.6000, 7210.90.9000, 7212.20.0000, 7212.30.1030, 7212.30.1090, 7212.30.3000, 7212.30.5000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7212.60.0000, 7215.90.1000, 7215.90.3000, 7215.90.5000, 7217.20.1500, 7217.30.1530,

7217.30.1560, 7217.90.1000, 7217.90.5030, 7217.90.5060, and 7217.90.5090.

Included in the order are flat-rolled products of nonrectangular cross-section where such cross-section is achieved subsequent to the rolling process (*i.e.*, products which have been "worked after rolling") -- for example, products which have been beveled or rounded at the edges.

Excluded from the scope of the order are flat-rolled steel products either plated or coated with tin, lead, chromium, chromium oxides, both tin and lead ("terne plate"), or both chromium and chromium oxides ("tin-free steel"), whether or not painted, varnished or coated with plastics or other nonmetallic substances in addition to the metallic coating. Also excluded from the scope of the order are clad products in straight lengths of 0.1875 inch or more in composite thickness and of a width which exceeds 150 mm and measures at least twice the thickness. Also excluded from the scope of the order are certain clad stainless flat-rolled products, which are three-layered corrosion-resistant carbon steel flat-rolled products less than 4.75 mm in composite thickness that consist of a carbon steel flat-rolled product clad on both sides with stainless steel in a 20% - 60% - 20% ratio. *See Antidumping Duty Order: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan*, 58 FR 44163 (August 19, 1993).

Exclusions due to Changed Circumstances Reviews

The Department has issued the following rulings to date:

Excluded from the scope of this order are imports of certain corrosion-resistant carbon steel flat products meeting the following specifications: widths ranging from 10 mm (0.394 inches) through 100 mm (3.94 inches); thicknesses, including coatings, ranging from 0.11 mm (0.004 inches) through 0.60 mm (0.024 inches); and a coating that is from 0.003 mm (0.00012 inches) through 0.005 mm (0.000196 inches) in thickness and that is comprised of three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Antidumping Duty Administrative Review, and Revocation in Part of Antidumping Duty Order*, 62 FR 66848 (December 22, 1997).

Also excluded from the scope of this order are imports of subject merchandise meeting all of the following criteria: (1) Widths ranging from 10 mm (0.394 inches) through 100 mm (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 mm (0.004 inches) through 0.60 mm (0.024 inches); and (3) a coating that is from 0.003 mm (0.00012 inches) through 0.005 mm (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of chromate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of chromate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Antidumping Duty Administrative Review, and Revocation in Part of Antidumping Duty Order*, 64 FR 14861 (March 29, 1999).

Also excluded from the scope of this order are: (1) Carbon steel flat products measuring 1.84 mm in thickness and 43.6 mm or 16.1 mm in width consisting of carbon steel coil (SAE 1008) clad with an aluminum alloy that is balance aluminum, 20% tin, 1% copper, 0.3% silicon, 0.15% nickel, less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys; and (2) carbon steel flat products measuring 0.97 mm in thickness and 20 mm in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% to 11% tin, 9% to 11% lead, less than 1% zinc, less than 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 45% to 55% lead, 38% to 50% PTFE, 3% to 5% molybdenum disulfide and less than 2% other materials. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 64 FR 57032 (October 22, 1999).

Also excluded from the scope of the order are imports of doctor blades meeting the following specifications: carbon steel coil or strip, plated with nickel phosphorous, having a thickness of 0.1524 mm (0.006 inches), a width between 31.75 mm (1.25 inches) and 50.80 mm (2.00 inches), a core hardness between 580 to 630 HV, a surface hardness between 900 - - 990 HV; the carbon steel coil or strip consists of the

following elements identified in percentage by weight: 0.90% to 1.05% carbon; 0.15% to 0.35% silicon; 0.30% to 0.50% manganese; less than or equal to 0.03% of phosphorous; less than or equal to 0.006% of sulfur; other elements representing 0.24%; and the remainder of iron. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 65 FR 53983 (September 6, 2000).

Also excluded from the scope of the order are imports of carbon steel flat products meeting the following specifications: carbon steel flat products measuring 1.64 mm in thickness and 19.5 mm in width consisting of carbon steel coil (SAE 1008) with a lining clad with an aluminum alloy that is balance aluminum; 10 to 15% tin; 1 to 3% lead; 0.7 to 1.3% copper; 1.8 to 3.5% silicon; 0.1 to 0.7% chromium; less than 1% other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 8778 (February 2, 2001).

Also excluded from the scope of the order are carbon steel flat products meeting the following specifications: (1) Carbon steel flat products measuring 0.975 mm in thickness and 8.8 mm in width consisting of carbon steel coil (SAE 1012) clad with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% – 11% tin, 9% – 11% lead, maximum 1% other materials and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 13% – 17% carbon, 13% – 17% aromatic polyester, with a balance (approx. 66% – 74%) of polytetrafluorethylene (“PTFE”); and (2) carbon steel flat products measuring 1.02 mm in thickness and 10.7 mm in width consisting of carbon steel coil (SAE 1008) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that is balance copper, 9% – 11% tin, 9% – 11% lead, less than 0.35% iron, and meeting the requirements of SAE standard 792 for Bearing and Bushing Alloys, the second layer consisting of 45% – 55% lead, 3% – 5% molybdenum disulfide, with a balance (approx. 40% – 52%) of PTFE. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 15075 (March 15, 2001).

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring 1.93 mm or 2.75 mm (0.076 inches or 0.108 inches) in thickness, 87.3 mm or 99 mm (3.437 inches or 3.900 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 0.3% antimony, 2.5% silicon, 1% maximum total other (including iron), and remainder aluminum. Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, clad with aluminum, measuring 1.75 mm (0.069 inches) in thickness, 89 mm or 94 mm (3.500 inches or 3.700 inches) in width, with a low carbon steel back comprised of: carbon under 8%, manganese under 0.4%, phosphorous under 0.04%, and sulfur under 0.05%; clad with aluminum alloy comprised of: 0.7% copper, 12% tin, 1.7% lead, 2.5% silicon, 0.3% antimony, 1% maximum total other (including iron), and remainder aluminum. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 66 FR 20967 (April 26, 2001).

Also excluded from this order are products meeting the following specifications: carbon steel coil or strip, measuring a minimum of and including 1.10 mm to a maximum of and including 4.90 mm in overall thickness, a minimum of and including 76.00 mm to a maximum of and including 250.00 mm in overall width, with a low carbon steel back comprised of: carbon under 0.10%, manganese under 0.40%, phosphorous under 0.04%, sulfur under 0.05%, and silicon under 0.05%; clad with aluminum alloy comprised of: under 2.51% copper, under 15.10% tin, and remainder aluminum as listed on the mill specification sheet. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 67 FR 7356 (February 19, 2002).

Also excluded from this order are products meeting the following specifications: (1) Diffusion-annealed, non-alloy nickel-plated carbon products, with a substrate of cold-rolled battery grade sheet (“CRBG”) with both sides of the CRBG initially electrolytically plated with pure, unalloyed nickel and subsequently

annealed to create a diffusion between the nickel and iron substrate, with the nickel plated coating having a thickness of 0–5 microns per side with one side equaling at least 2 microns; and with the nickel carbon sheet having a thickness of from 0.004” (0.10 mm) to 0.030” (0.762 mm) and conforming to the following chemical specifications (%): C <= 0.08; Mn <= 0.45; P <= 0.02; S <= 0.02; Al <= 0.15; and Si <= 0.10; and the following physical specifications: Tensile = 65 KSI maximum; Yield = 32 – 55 KSI; Elongation = 18% minimum (aim 34%); Hardness = 85 – 150 Vickers; Grain Type = Equiaxed or Pancake; Grain Size (ASTM) = 7–12; Delta r value = aim less than +/- 0.2; Lankford value = <= 1.2.; and (2) next generation diffusion-annealed nickel plate meeting the following specifications: (a) nickel-graphite plated, diffusion-annealed, tin-nickel plated carbon products, with a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion-annealed tin-nickel plated carbon steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of mixture of natural nickel and graphite then electrolytically plated on the top side of the strip of the nickel-tin alloy; having a coating thickness: top side: nickel-graphite, tin-nickel layer <= 1.0 micrometers; tin layer only <= 0.05 micrometers, nickel-graphite layer only <= 0.2 micrometers, and bottom side: nickel layer <= 1.0 micrometers; (b) nickel-graphite, diffusion-annealed, nickel plated carbon products, having a natural composition mixture of nickel and graphite electrolytically plated to the top side of diffusion-annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; with both sides of the cold rolled base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the

substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer ≤ 1.0 micrometers; nickel-graphite layer ≤ 0.5 micrometers; bottom side: nickel layer ≤ 1.0 micrometers; (c) diffusion-annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer ≤ 1.0 micrometers; bottom side: nickel layer ≤ 1.0 micrometers; (d) nickel-phosphorous plated diffusion-annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion-annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer ≤ 1.0 micrometers; nickel-phosphorous layer ≤ 0.1 micrometers; bottom side: nickel layer ≤ 1.0 micrometers; (e) diffusion-annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion-annealed tin-nickel plated cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically

plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin - nickel combination layer ≤ 1.0 micrometers; tin layer only ≤ 0.05 micrometers; bottom side: nickel layer ≤ 1.0 micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer ≤ 1 micrometer; tin layer alone ≤ 0.05 micrometers; bottom side: nickel layer ≤ 1.0 micrometer. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 67 FR 47768 (July 22, 2002).

Also excluded from this order are products meeting the following specifications: (1) Widths ranging from 10 mm (0.394 inches) through 100 mm (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 mm (0.004 inches) through 0.60 mm (0.024 inches); and (3) a coating that is from 0.003 mm (0.00012 inches) through 0.005 mm (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of phosphate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of phosphate, and finally a layer consisting of silicate. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of*

Antidumping Duty Order, 67 FR 57208 (September 9, 2002).

Also excluded from this order are products meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40% by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer of iron-zinc alloy by electro-galvanizing process, having an effective amount of zinc up to 40% by weight, and (2) corrosion resistant continuously annealed flat-rolled products, continuous cast, the foregoing with chemical composition (percent by weight): carbon not over 0.06% by weight, manganese 0.20 or more but not over 0.40, phosphorus not over 0.02, sulfur not over 0.023, silicon not over 0.03, aluminum 0.03 or more but not over 0.08, arsenic not over 0.02, copper not over 0.08 and nitrogen 0.003 or more but not over 0.008; and meeting the characteristics described below: (A) Products with one side coated with a nickel-iron - diffused layer which is less than 1 micrometer in thickness and the other side coated with a two-layer coating composed of a base nickel-iron - diffused coating layer and a surface coating layer of annealed and softened pure nickel, with total coating thickness for both layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with scanning electron microscope (SEM) not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (B) products having one side coated with a nickel-iron - diffused layer which is less than 1 micrometer in thickness and the other side coated with a four-layer coating composed of a base nickel-iron - diffused coating layer; with an inner middle coating layer of annealed and softened pure nickel, an outer middle surface coating layer of hard nickel and a topmost nickel-phosphorus - plated layer; with combined coating thickness for the four layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; (C) products having

one side coated with a nickel-iron - diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron - diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, luster-agent - added nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; with SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length; or (D) products having one side coated with a nickel-iron - diffused layer which is less than 1 micrometer in thickness and the other side coated with a three-layer coating composed of a base nickel-iron - diffused coating layer, with a middle coating layer of annealed and softened pure nickel and a surface coating layer of hard, pure nickel which is not heat-treated; with combined coating thickness for all three layers of more than 2 micrometers; surface roughness (RA-microns) 0.18 or less; SEM not revealing oxides greater than 1 micron; and inclusion groups or clusters shall not exceed 5 microns in length. *See Certain Corrosion-Resistant Carbon Steel Flat Products From Japan: Notice of Final Results of Changed Circumstances Review, and Revocation in Part of Antidumping Duty Order*, 68 FR 19970 (April 23, 2003).

Also excluded from the scope of this order is merchandise meeting the following specifications: (1) Base metal: Aluminum Killed, Continuous Cast, Carbon Steel SAE 1008, (2) Chemical Composition: Carbon 0.08% max., Silicon, 0.03% max., Manganese 0.40% max., Phosphorus, 0.02% max., Sulfur 0.02% max., (3) Nominal thickness of 0.054 mm, (4) Thickness Tolerance minimum 0.0513 mm, maximum 0.0567 mm, (5) Width of 600 mm or greater, and (7) Nickel plate min. 2.45 microns per side. *See Notice of Final Results of Changed Circumstances Review and Revocation, in Part: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan*, 70 FR 2608 (January 14, 2005).

Also excluded from the scope of this order are the following 24 separate corrosion-resistant carbon steel coil products meeting the following specifications:

Product 1 Products described in industry usage as of carbon steel, measuring 1.625 mm to 1.655 mm in thickness and 19.3 mm to 19.7 mm in width, consisting of carbon steel coil (SAE 1010) with a lining clad with an

aluminum alloy containing by weight 10% or more but not more than 15% of tin, 1% or more but not more than 3% of lead, 0.7% or more but not more than 1.3% of copper, 1.8% or more but not more than 3.5% of silicon, 0.1% or more but not more than 0.7% of chromium and less than or equal to 1% of other materials, and meeting the requirements of SAE standard 788 for Bearing and Bushing Alloys.

Product 2 Products described in industry usage as of carbon steel, measuring 0.955 mm to 0.985 mm in thickness and 8.6 mm to 9.0 mm in width, consisting of carbon steel coil (SAE 1012) clad with a two-layer lining, the first layer consisting of a copper-lead alloy powder that contains by weight 9% or more but not more than 11% of tin, 9% or more but not more than 11% of lead, less than 0.05% phosphorus, less than 0.35% iron and less than or equal to 1% other materials, and meeting the requirements of SAE standard 797 for Bearing and Bushing Alloys, with the second layer containing by weight 13% or more but not more than 17% of carbon, 13% or more but not more than 17% of aromatic polyester, and the remainder (approx. 66-74%) of PTFE.

Product 3 Products described in industry usage as of carbon steel, measuring 1.01 mm to 1.03 mm in thickness and 10.5 mm to 10.9 mm in width, consisting of carbon steel coil (SAE 1010) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that contains by weight 9% or more but not more than 11% of tin, 9% or more but not more than 11% of lead, less than 1% zinc and less than or equal to 1% other materials, and meeting the requirements of SAE standard 797 for Bearing and Bushing Alloys, with the second layer containing by weight 45% or more but not more than 55% of lead, 3% or more but not more than 5% of molybdenum disulfide, and the remainder made up of PTFE (approximately 38% to 52%) and less than 2% in the aggregate of other materials.

Product 4 Products described in industry usage as of carbon steel, measuring 1.8 mm to 1.88 mm in thickness and 43.4 mm to 43.8 mm or 16.1 mm to 1.65 mm in width, consisting of carbon steel coil (SAE 1010) clad with an aluminum alloy that contains by weight 19% to 20% tin, 1% to 1.2% copper, less than 0.3% silicon, 0.15% nickel and less than 1% in the aggregate other materials and meeting the requirements of SAE standard 783 for Bearing and Bushing Alloys.

Product 5 Products described in industry usage as of carbon steel,

measuring 0.95 mm to 0.98 mm in thickness and 19.95 mm to 20 mm in width, consisting of carbon steel coil (SAE 1010) with a two-layer lining, the first layer consisting of a copper-lead alloy powder that contains by weight 9% or more but not more than 11% of tin, 9% or more but not more than 11% of lead, less than 1% of zinc and less than or equal to 1% in the aggregate of other materials and meeting the requirements of SAE standard 797 for Bearing and Bushing Alloys, with the second layer consisting by weight of 45% or more but not more than 55% of lead, 3% or more but not more than 5% of molybdenum disulfide and with the remainder made up of PTFE (approximately 38% to 52%) and up to 2% in the aggregate of other materials.

Product 6 Products described in industry usage as of carbon steel, measuring 0.96 mm to 0.98 mm in thickness and 18.75 mm to 18.95 mm in width; base of SAE 1010 steel with a two-layer lining, the first layer consisting of copper-base alloy powder with chemical composition (percent by weight): tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35, and other materials less than 1%; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of lead 33 to 37%, aromatic polyester 28 to 32%, and other materials less than 2% with a balance of PTFE.

Product 7 Products described in industry usage as of carbon steel, measuring 1.21 mm to 1.25 mm in thickness and 19.4 mm to 19.6 mm in width; base of SAE 1012 steel with lining of copper base alloy with chemical composition (percent by weight): tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35 and other materials less than 1%; meeting the requirements of SAE standard 797 for bearing and bushing alloys.

Product 8 Products described in industry usage as of carbon steel, measuring 0.96 mm to 0.98 mm in thickness and 21.5 mm to 21.7 mm in width; base of SAE 1010 steel with a two-layer lining, the first layer consisting of copper-base alloy powder with chemical composition (percent by weight): tin 9 to 11, lead 9 to 11, phosphorus less than 0.05%, ferrous group less than 0.35 and other materials less than 1; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of (percent by weight) lead 33 to 37, aromatic polyester 28 to 32 and other materials less than 2 with a balance of PTFE.

Product 9 Products described in industry usage as of carbon steel, measuring 0.96 mm to 0.99 mm in thickness and 7.65 mm to 7.85 mm in width; base of SAE 1012 steel with a two-layer lining, the first layer consisting of copper-based alloy powder with chemical composition (percent by weight): tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35 and other materials less than 1; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of (percent by weight) carbon 13 to 17 and aromatic polyester 13 to 17, with a balance of

polytetrafluoroethylene ("PTFE")
Product 10 Products described in industry usage as of carbon steel, measuring 0.955 mm to 0.985 mm in thickness and 13.6 mm to 14 mm in width; base of SAE 1012 steel with a two-layer lining, the first layer consisting of copper-based alloy powder with chemical composition (percent by weight): tin 9 to 11, lead 9 to 11, phosphorus less than 0.05, ferrous group less than 0.35 and other materials less than 1; meeting the requirements of SAE standard 797 for bearing and bushing alloys; the second layer consisting of (percent by weight) carbon 13 to 17, aromatic polyester 13 to 17, with a balance (approximately 66 to 74) of PTFE.

Product 11 Products described in industry usage as of carbon steel, measuring 1.2 mm to 1.24 mm in thickness; 20 mm to 20.4 mm in width; consisting of carbon steel coils (SAE 1012) with a lining of sintered phosphorus bronze alloy with chemical composition (percent by weight): tin 5.5 to 7; phosphorus 0.03 to 0.35; lead less than 1 and other non-copper materials less than 1.

Product 12 Products described in industry usage as of carbon steel, measuring 1.8 mm to 1.88 mm in thickness and 43.3 mm to 43.7 mm in width; base of SAE 1010 steel with a lining of aluminum based alloy with chemical composition (percent by weight): tin 10 to 15, lead 1 to 3, copper 0.7 to 1.3, silicon 1.8 to 3.5, chromium 0.1 to 0.7 and other materials less than 1; meeting the requirements of SAE standard 788 for bearing and bushing alloys.

Product 13 Products described in industry usage as of carbon steel, measuring 1.8 mm to 1.88 mm in thickness and 24.2 mm to 24.6 mm in width; base of SAE 1010 steel with a lining of aluminum alloy with chemical composition (percent by weight): tin 10

to 15, lead 1 to 3, copper 0.7 to 1.3, silicon 1.8 to 3.5, chromium 0.1 to 0.7 and other materials less than 1; meeting the requirements of SAE standard 788 for bearing and bushing alloys.

Product 14 Flat-rolled coated SAE 1009 steel in coils, with thickness not less than 0.915 mm but not over 0.965 mm, width not less than 19.75 mm or more but not over 20.35 mm; with a two-layer coating; the first layer consisting of tin 9 to 11%, lead 9 to 11%, zinc less than 1%, other materials (other than copper) not over 1% and balance copper; the second layer consisting of lead 45 to 55%, molybdenum disulfide (MoS₂) 3 to 5%, other materials not over 2%, balance PTFE.

Product 15 Flat-rolled coated SAE 1009 steel in coils with thickness not less than 0.915 mm or more but not over 0.965 mm; width not less than 18.65 mm or more but not over 19.25 mm; with a two-layer coating; the first layer consisting of tin 9 to 11%, lead 9 to 11%, zinc less than 1%, other materials (other than copper) not over 1%, balance copper; the second layer consisting of lead 33 to 37%, aromatic polyester 13 to 17%, other materials other than PTFE less than 2%, balance PTFE.

Product 16 Flat-rolled coated SAE 1009 steel in coils with thickness not less than 0.920 mm or more but not over 0.970 mm; width not less than 21.35 mm or more but not over 21.95 mm; with a two-layer coating; the first layer consisting of tin 9 to 11%, lead 9 to 11%, zinc less than 1%, other materials (other than copper) not over 1%, balance copper; the second layer consisting of lead 33 to 37%, aromatic polyester 13 to 17%, other materials (other than PTFE) less than 2%, balance PTFE.

Product 17 Flat-rolled coated SAE 1009 steel in coils with thickness not less than 1.80 mm or more but not over 1.85 mm, width not less than 14.7 mm or more but not over 15.3 mm; with a lining consisting of tin 2.5 to 4.5%, lead 21.0 to 25.0%, zinc less than 3%, iron less than 0.35%, other materials (other than copper) less than 1%, balance copper.

Product 18 Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 14.5 mm or more but not over 15.1 mm; with a lining consisting of tin 2.3 to 4.2%, lead 20 to 25%, iron 1.5 to 4.5%, phosphorus 0.2 to 2.0%, other materials (other than copper) less than 1%, balance copper.

Product 19 Flat-rolled coated SAE 1009 steel in coils with thickness not less

than 1.75 mm or more but not over 1.8 mm; width not less than 18.0 mm or more but not over 18.6 mm; with a lining consisting of tin 2.3 to 4.2%, lead 20 to 25%, iron 1.5 to 4.5%, phosphorus 0.2 to 2.0%, other materials (other than copper) less than 1%, balance copper.

Product 20 Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 13.6 mm or more but not over 14.2 mm; with a lining consisting of tin 2.3 to 4.2%, lead 20 to 25%, iron 1.5 to 4.5%, phosphorus 0.2 to 2.0%, other materials (other than copper) less than 1%, with a balance copper.

Product 21 Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 11.5 mm or more but not over 12.1 mm; with a lining consisting of tin 2.3 to 4.2%, lead 20 to 25%, iron 1.5 to 4.5%, phosphorus 0.2 to 2.0%, other materials (other than copper) less than 1%, balance copper.

Product 22 Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 11.2 mm or more but not over 11.8 mm, with a lining consisting of copper 0.7 to 1.3%, tin 17.5 to 22.5%, silicon less than 0.3%, nickel less than 0.15%, other materials less than 1%, balance aluminum.

Product 23 Flat-rolled coated SAE 1009 steel in coils with thickness 1.59 mm or more but not over 1.64 mm; width 7.2 mm or more but not over 7.8 mm; with a lining consisting of copper 0.7 to 1.3%, tin 17.5 to 22.5%, silicon less than 0.3%, nickel less than 0.15%, other materials (other than copper) less than 1%, balance copper.

Product 24 Flat-rolled coated SAE 1009 steel in coils with thickness 1.72 mm or more but not over 1.77 mm; width 7.7 mm or more but not over 8.3 mm; with a lining consisting of copper 0.7 to 1.3%, tin 17.5 to 22.5%, silicon less than 0.3%, nickel less than 0.15%, other materials (other than copper) less than 1%, balance copper. *See Notice of Final Results of Antidumping Duty Changed Circumstances Review and Revocation, In Part: Certain Corrosion-Resistant Carbon Steel Flat Products From Japan, 70 FR 5137 (February 1, 2005).*

Merchandise requested for Exclusion from the Scope of the Order

Metal One requested that certain diffusion-annealed nickel-plate products meeting the following specifications be excluded from the scope of the order:

Short description	Diffusion-annealed, non-alloy nickel-plated steel sheet (cold rolled battery grade sheet or CRBG) with an unalloyed nickel plated coating.
Thickness of nickel-plated coating	0 – 8 microns with both sides having a coating of at least 0.2 microns.
Thickness of CRBG	0.035 mm to 0.762 mm.
Chemical Specifications:	
Carbon (C)	≤ 0.03
Manganese (Mn)	≤ 0.60
Phosphorus (P)	≤ 0.04
Sulfur (S)	≤ 0.04
Aluminum (Al)	< 0.15
Silicon (Si)	< 0.10
Mechanical Specifications:	
Tensile strength	≤ 70 KSI Maximum
Yield	22 – 55 KSI
Elongation	18% Minimum
Hardness	85 – 150 Vickers
Grain Type	Equiaxed or Pancake
Grain Size (ASTM)	7 – 12
Delta r value	+/- 0.3
Lankford value	≥ 0.7

Preliminary Results of Changed Circumstances Review

Pursuant to section 751(d) of the Tariff Act of 1930, as amended, (“the Act”), the Department may revoke an antidumping duty order based on a review under section 751(b) of the Act. 19 CFR 351.222(g)(1)(i) provides that the Department may revoke an order, in whole or in part, based on changed circumstances if “(p)roducers accounting for substantially all of the production of the domestic like product to which the order (or part of the order to be revoked) have expressed a lack of interest in the order, in whole or in part.” See also section 781(h)(2) of the Act. In this context, the Department has interpreted “substantially all” production normally to mean at least 85 percent of domestic production of the like product. See *Oil Country Tubular Goods from Mexico: Preliminary Results of Changed Circumstances Antidumping Duty Administrative Review*, 64 FR 14213, 14214 (March 24, 1999). See also *Certain Tin Mill Products from Japan: Final Results of Changed Circumstances Review*, 66 FR 52109, 52110 (October 12, 2001). U.S. Steel objects to the revocation, in part, of the order and claims that it constitutes over 15 percent of the total domestic production. See *Letter from U.S. Steel*, December 27, 2004.

Metal One has not shown, as required by 351.222(g)(1)(i) of the Department’s regulations, that producers accounting for substantially all of the production of the domestic like product have expressed a lack of interest in the order. Therefore, the Department preliminarily determines that there is insufficient evidence to warrant exclusion of the products included in Metal One’s

changed circumstances review request from the scope of the order.

As Metal One has not met the requirement showing that substantially all of the producers of the domestic like product are no longer interested in the products included in Metal One’s changes circumstances review request, Metal One’s claim that its products is similar to products already excluded from the order is moot.

Public Comment

Any interested party may request a hearing within 10 days of publication of this notice. See 19 CFR 351.310(c). Any hearing, if requested, will be held 21 days after the date of publication of this notice, or the first working day thereafter. Interested parties may submit case briefs and/or written comments no later than 14 days after the date of publication of this notice. See 19 CFR 351.309(c)(ii). Rebuttal briefs and rebuttals to written comments, which must be limited to issues raised in such briefs or comments, may be filed no later than 19 days after the date of publication of this notice. See 19 CFR 351.309(d). Parties who submit arguments are requested to submit with the argument (1) a statement of the issue, (2) a brief summary of the argument, and (3) a table of authorities.

Consistent with 19 CFR 351.216(e), we will issue the final results of this changed circumstances review no later than 270 days after the date on which this review was initiated.

We are issuing and publishing this notice in accordance with sections 751(b)(1) and 777(I)(1) of the Act and 19 CFR 351.216.

Dated: June 15, 2005.

Joseph A. Spetrini,

Acting Assistant Secretary for Import Administration.

[FR Doc. E5-3211 Filed 6-20-05; 8:45 am]

BILLING CODE 3510-DS-S

DEPARTMENT OF COMMERCE

International Trade Administration

[A-485-803]

Notice of Final Results of Antidumping Duty Changed Circumstances Review: Certain Cut-to-Length Carbon Steel Plate from Romania

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

SUMMARY: On May 3, 2005, the Department of Commerce (“the Department”) published a notice of initiation and the preliminary results of its changed circumstances review of the antidumping duty finding on certain cut-to-length carbon steel plate (“carbon steel plate”) from Romania in which we preliminarily determined that Mittal Steel Galati S.A. (“Mittal Steel”) is the successor-in-interest to the S.C. Ispat Sidex S.A. (“Sidex”). See *Certain Cut-to-Length Carbon Steel Plate from Romania: Initiation and Preliminary Results of Changed Circumstances Antidumping Duty Administrative Review*, 70 FR 22847 (May 3, 2005) (“*Preliminary Results*”). We gave interested parties the opportunity to comment on the *Preliminary Results*. We received no comments. Therefore, for these final results, the Department is adopting its preliminary determination that Mittal Steel is the successor-in-interest to Sidex.