

(d) *Application for change of nonimmigrant classification from that of a student under section 101(a)(15)(M)(i) to that described in section 101(a)(15)(H).* A district director shall deny an application for change of nonimmigrant classification from that of an M–1 student to that of an alien temporary worker under section 101(a)(15)(H) of the Act if the education or training which the student received while an M–1 student enables the student to meet the qualifications for temporary worker classification under section 101(a)(15)(H) of the Act.

(e) *Change of nonimmigrant classification to that as described in section 101(a)(15)(N).* An application for change to N status shall not be denied on the grounds the applicant is an intending immigrant. Change of status shall be granted for three years not to exceed termination of eligibility under section 101(a)(15)(N) of the Act. Employment authorization pursuant to section 274(A) of the Act may be granted to an alien accorded nonimmigrant status under section 101(a)(15)(N) of the Act. Employment authorization is automatically terminated when the alien changes status or is no longer eligible for classification under section 101(a)(15)(N) of the Act.

Alejandro N. Mayorkas,
Secretary of Homeland Security.

[FR Doc. 2021–05357 Filed 3–11–21; 4:15 pm]

BILLING CODE 9111–97–P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 25

[Docket No. FAA–2019–1055; Special Conditions No. 25–778–SC]

Special Conditions: Boeing Commercial Airplanes Model 777–9 Airplanes; Structure-Mounted Airbags

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions.

SUMMARY: These special conditions are issued for the Boeing Commercial Airplanes (Boeing) Model 777–9 airplane. This airplane will have a novel or unusual design feature when compared to the state of technology envisioned in the airworthiness standards for transport-category airplanes. This design feature is structure-mounted airbags designed to limit occupant forward excursion in the event of an emergency landing. The

applicable airworthiness regulations do not contain adequate or appropriate safety standards for this design feature. These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

DATES: Effective April 14, 2021.

FOR FURTHER INFORMATION CONTACT: Shannon Lennon, Airframe and Cabin Safety Section, AIR–675, Transport Standards Branch, Policy and Innovation Division, Aircraft Certification Service, Federal Aviation Administration, 2200 South 216th Street, Des Moines, Washington 98198; telephone and fax 206–231–3209; email shannon.lennon@faa.gov.

SUPPLEMENTARY INFORMATION:

Background

On December 6, 2013, Boeing applied for a change to Type Certificate No. T00001SE for structure-mounted airbags installed in the Boeing Model 777–9 airplane. The application date was extended to March 30, 2016, based on Boeing's request. The Boeing Model 777–9 airplane, which is a derivative of the Boeing Model 777 airplane currently approved under Type Certificate No. T00001SE, is a twin-engine, transport-category airplane with seating for 495 passengers and a maximum takeoff weight of 775,000 pounds.

Type Certification Basis

Under the provisions of title 14, Code of Federal Regulations (14 CFR) 21.101, Boeing must show that the Model 777–9 airplane, as changed, continues to meet the applicable provisions of the regulations listed in Type Certificate No. T00001SE, or the applicable regulations in effect on the date of application for the change, except for earlier amendments as agreed upon by the FAA.

If the Administrator finds that the applicable airworthiness regulations (e.g., 14 CFR part 25) do not contain adequate or appropriate safety standards for the Boeing Model 777–9 airplane because of a novel or unusual design feature, special conditions are prescribed under the provisions of § 21.16.

Special conditions are initially applicable to the model for which they are issued. Should the type certificate for that model be amended later to include any other model that incorporates the same novel or unusual design feature, or should any other model already included on the same type certificate be modified to

incorporate the same novel or unusual design feature, these special conditions would also apply to the other model under § 21.101.

In addition to the applicable airworthiness regulations and special conditions, the Boeing Model 777–9 airplane must comply with the fuel-vent and exhaust-emission requirements of 14 CFR part 34, and the noise-certification requirements of 14 CFR part 36.

The FAA issues special conditions, as defined in 14 CFR 11.19, in accordance with § 11.38, and they become part of the type certification basis under § 21.101.

Novel or Unusual Design Features

The Boeing Model 777–9 airplane will incorporate the following novel or unusual design features:

Airbags mounted to structure to prevent head injury.

Discussion

Boeing will install structure-mounted airbags instead of inflatable lap belts as a means to protect each occupant from serious injury in the event of an emergency landing, as required by § 25.562(c)(5), on 777–9 airplanes.

Such use of airbags to provide injury protection for the occupant is a novel or unusual feature for this airplane model, and the applicable airworthiness regulations do not contain adequate or appropriate airworthiness standards for these design features. Therefore, special conditions are needed to address requirements particular to installation of airbags in this manner.

Special conditions exist for airbags installed on seat belts, known as inflatable lap belts, which have been installed on Boeing airplane passenger seats. Structure-mounted airbags, although a novel design, were first introduced on Jetstream Aircraft Limited Model 4100 series airplanes, which resulted in issuance of Special Conditions 25–ANM–127 on May 14, 1997. These special conditions supplemented 14 CFR part 25 and, more specifically, §§ 25.562 and 25.785.

The structure-mounted airbag, similar to the inflatable lap belt, is designed to limit occupant forward excursion in the event of an emergency landing. These airbags will reduce the potential for serious injury, including reducing the head-injury criterion measurement defined in part 25. However, structure-mounted airbags function similarly as automotive airbags, where the airbag deploys from furniture located in front of the passenger, relative to the airplane's direction of flight, forming a barrier between the structure and

occupant. Also, unlike the inflatable lap belt, the structure-mounted airbag does not move with the occupant. To account for out-of-position and brace-position occupants, the airbag is designed to conform to the curvature of the exposed structure in the head-strike zone.

Because the airbag system is essentially a single-use device, it could deploy under crash conditions that are not sufficiently so severe as to require the injury protection the airbag system provides. Because an actual crash is frequently composed of a series of impacts before the airplane comes to rest, a larger impact following the initial impact could render the airbag system unavailable. This potential situation does not exist with standard upper-torso restraints, which tend to provide continuous protection regardless of impact severity, or number of impacts, in a crash event. Therefore, the airbag-system installation should be such that it provides protection, when it is required, by not expending its protection when it is not required. If the airbag deployment threshold is unnecessarily low, the airbag would need to continue to provide protection when an impact requiring protection occurs.

These special conditions are based upon special conditions 25–605–SC for the Boeing Model 787–9 airplanes equipped with B/E Aerospace Super-Diamond model business-class passenger seats and associated furniture.

The special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

Discussion of Comments

The FAA issued Notice of Proposed Special Conditions No. 25–20–05–SC for the Boeing Model 777–9 airplane, which was published in the **Federal Register** on July 22, 2020 (85 FR 44244). No comments were received, and the special conditions are adopted as proposed.

Applicability

As discussed above, these special conditions are applicable to the Boeing Model 777–9 airplane. Should Boeing apply at a later date for a change to the type certificate to include another model incorporating the same novel or unusual design feature, these special conditions would apply to that model as well.

Conclusion

This action affects only certain novel or unusual design features on one model

of airplane. It is not a rule of general applicability.

List of Subjects in 14 CFR Part 25

Aircraft, Aviation safety, Reporting and recordkeeping requirements.

Authority Citation

The authority citation for these special conditions is as follows:

Authority: 49 U.S.C. 106(f), 106(g), 40113, 44701, 44702, 44704.

The Special Conditions

Accordingly, pursuant to the authority delegated to me by the Administrator, the following special conditions are issued as part of the type certification basis for Boeing Model 777–9 airplanes.

1. The applicant must demonstrate by test that the structure-mounted airbag will deploy and provide protection under crash conditions where it is necessary to prevent serious injury to a 50th percentile occupant, as specified in § 25.562. The means of protection must provide a consistent approach to energy absorption for a range of occupants, from a two-year-old child to a 95th percentile male.

2. The structure-mounted airbag must provide adequate protection for each occupant regardless of the number of occupants of the seat assembly.

3. The structure-mounted airbag system must not be susceptible to inadvertent deployment as a result of wear and tear, or inertial loads resulting from in-flight or ground maneuvers (including gusts and hard landings) likely to be experienced in service.

4. Deployment of the structure-mounted airbag must not introduce hazards or injury mechanisms to the seated occupant, including occupants in the brace position. Deployment of the structure-mounted airbag must also not result in injuries that could impede rapid exit from the airplane.

5. The applicant must demonstrate that an inadvertent deployment that could cause injury to a standing or sitting person is improbable. Inadvertent deployment must not cause injury to anyone who may be positioned close to the structure-mounted airbag (e.g., seated in an adjacent seat, or standing adjacent to the airbag installation or the subject seat). Cases where a structure-mounted airbag is inadvertently deployed near a seated occupant or an empty seat must be considered.

6. Effects of the deflection and deformation of the structure to which the airbag is attached must be taken into account when evaluating deployment and location of the inflated airbag. The effect of loads imposed by airbag

deployment, or stowed components where applicable, must also be taken into account.

7. Inadvertent deployment of the structure-mounted airbag during the most critical part of flight will either not cause a hazard to the airplane or is extremely improbable.

8. The applicant must demonstrate that the structure-mounted airbag, when deployed, does not impair access to the seatbelt- or harness-release means, and must not hinder evacuation. This will include consideration of adjacent seat places and the aisle.

9. The airbag, once deployed, must not adversely affect the emergency-lighting system, and must not block escape-path lighting to the extent that the light(s) no longer meet their intended function.

10. The structure-mounted airbag must not impede occupants' rapid exit from the airplane 10 seconds after its deployment.

11. Where structure-mounted airbag systems are installed in or close to passenger evacuation routes (other than for the passenger seat for which the airbag is installed), possibility of impact on emergency evacuation (e.g., hanging in the aisle, potential trip hazard, etc.) must be evaluated.

12. The airbag electronic system must be designed to be protected from lightning per § 25.1316(b), and high-intensity radiated fields per § 25.1317(c).

13. The structure-mounted airbag system must not contain or release hazardous quantities of gas or particulate matter into the cabin.

14. The structure-mounted airbag installation must be protected from the effects of fire such that no hazard to occupants will result.

15. The inflatable bag material must meet the 2.5-inches-per-minute horizontal flammability test defined in 14 CFR part 25, appendix F, part I, paragraph (a)(1)(iv).

16. The design of the structure-mounted airbag system must protect the mechanisms and controls from external contamination associated with that which could occur on or around passenger seating.

17. The structure-mounted airbag system must have a means to verify the integrity of the structure-mounted airbag activation system.

18. The applicant must provide installation limitations to ensure installation compatibility between the seat design and opposing monument or structure.

Issued in Des Moines, Washington, on January 5, 2021.

Suzanne Masterson,

Manager, Transport Airplane Strategic Policy Section, Policy and Innovation Division, Aircraft Certification Service.

[FR Doc. 2021-05308 Filed 3-12-21; 8:45 am]

BILLING CODE 4910-13-P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 25

[Docket No. FAA-2020-0404; Special Conditions No. 25-783-SC]

Special Conditions: B/E Aerospace, Bombardier Model CL-600-2B16 (604 Variant) Airplane; Seats With Pretensioner Restraint Systems

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions.

SUMMARY: These special conditions are issued for the Bombardier Inc. (Bombardier) Model CL-600-2B16 (604 variant) airplane. This airplane, as modified by B/E Aerospace, will have a novel or unusual design feature when compared to the state of technology envisioned in the airworthiness standards for transport category airplanes. This design feature is seats with a 3-point shoulder harness incorporating a pretensioner restraint system. The applicable airworthiness regulations do not contain adequate or appropriate safety standards for this design feature. These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

DATES: Effective on B/E Aerospace on March 15, 2021.

FOR FURTHER INFORMATION CONTACT: Shannon Lennon, Human-Machine Interface Section, AIR-626, Technical Innovation Policy Branch, Policy and Innovation Division, Aircraft Certification Service, Federal Aviation Administration, 2200 South 216th Street, Des Moines, Washington 98198; telephone and fax 206-231-3209; email shannon.lennon@faa.gov.

SUPPLEMENTARY INFORMATION:

Background

On June 7, 2019, B/E Aerospace applied for a supplemental type certificate for seats with 3-point harness and pretensioner restraint systems on Bombardier Model CL-600-2B16 (604 variant) airplanes. The 604 variant is a

derivative of the Bombardier Model CL-600-2B16 airplane currently approved under Type Certificate No. A21EA. This airplane variant is a twin-engine, transport category airplane with seating for 22 passengers, including crew, and a maximum take-off weight of 47,600 pounds.

Type Certification Basis

Under the provisions of title 14, Code of Federal Regulations (14 CFR) 21.101, B/E Aerospace must show that the Bombardier Model CL-600-2B16 (604 variant) airplane, as changed, continues to meet the applicable provisions of the regulations listed in Type Certificate No. A21EA or the applicable regulations in effect on the date of application for the change, except for earlier amendments as agreed upon by the FAA.

If the Administrator finds that the applicable airworthiness regulations (e.g., 14 CFR part 25) do not contain adequate or appropriate safety standards for the Bombardier Model CL-600-2B16 (604 variant) airplane because of a novel or unusual design feature, special conditions are prescribed under the provisions of § 21.16.

Special conditions are initially applicable to the model for which they are issued. Should the applicant apply for a supplemental type certificate to modify any other model included on the same type certificate to incorporate the same novel or unusual design feature, these special conditions would also apply to the other model under § 21.101.

In addition to the applicable airworthiness regulations and special conditions, the Bombardier Model CL-600-2B16 (604 variant) airplane must comply with the fuel-vent and exhaust-emission requirements of 14 CFR part 34, and the noise-certification requirements of 14 CFR part 36.

The FAA issues special conditions, as defined in 14 CFR 11.19, in accordance with § 11.38, and they become part of the type certification basis under § 21.101.

Novel or Unusual Design Features

The Bombardier Model CL-600-2B16 (604 variant) airplane, as modified by B/E Aerospace, will incorporate the following novel or unusual design feature:

Seats with a 3-point shoulder harness incorporating a pretensioner restraint system to prevent head injuries.

Discussion

B/E Aerospace has developed a system in which a pretensioning automotive retractor eliminates slack in the 3-point shoulder harness, pulling the occupant back into the seat prior to

impact. This has the effect of reducing forward translation of the occupant (reduced head arc), while reducing the loads in the shoulder harness. B/E Aerospace will install, in Bombardier Model CL-600-2B16 (604 variant) airplanes, seats that incorporate a 3-point harness and pretensioner restraint system to protect seat occupants from head injuries.

Over the past 10 years, multiple sensor-driven systems have been installed in various airplanes to meet improved crashworthiness regulations. A sensor-driven system is defined as any system that activates due to a signal sent by an impact-triggered inertial sensor. These types of systems include a lap-belt airbag, a structure-mounted airbag, and a 3-point harness and pretensioner restraint system.

Shoulder harnesses have been widely used on flight-attendant seats, flight-deck seats, in business jets, and in general-aviation airplanes to reduce occupant head injury in the unlikely event of an emergency landing. Special conditions, pertinent regulations, and guidance have been published, relating to other or existing restraint systems. However, the use of a pretensioner restraint system with a 3-point harness on transport airplane seats is a novel design.

Pretensioner technology involves a step change in loading experienced by the occupant for impacts below and above that at which the device activates, because the upper torso excursion would be interrupted by activation of the shoulder harness. This could result in the head-injury criteria being higher at an intermediate impact condition than that resulting from the maximum impact condition corresponding to the test conditions specified in § 25.562.

The ideal triangular maximum-severity pulse is defined in Advisory Circular 25.562-1B, "Dynamic Evaluation of Seat Restraint Systems and Occupant Protection on Transport Airplanes with Change 1," dated January 10, 2006. For evaluating and testing less-severe pulses to assess the effectiveness of the pretensioner setting, a similar triangular pulse should be used with acceleration, rise time, and velocity change scaled accordingly. The magnitude of the required pulse should not deviate below the ideal pulse by more than 0.5g until 1.33 t_1 is reached, where t_1 represents the time interval between 0 and t_1 on the referenced pulse shape as shown in AC 25.562-1B. This is an acceptable method of compliance to the test requirements of these special conditions.

Additionally, the pretensioner might not provide protection, after actuation,