

inch, with widths of 27.0 inches or 31.5 inches, and with T-1 temper properties.

- Single reduced electrolytically chromium coated steel, with a chemical composition of 0.005% max carbon, 0.030% max silicon, 0.25% max manganese, 0.025% max phosphorous, 0.025% max sulfur, 0.070% max aluminum, and the balance iron, with a metallic chromium layer of 70–130 mg/m², with a chromium oxide layer of 5–30 mg/m², with a tensile strength of 260–440 N/mm², with an elongation of 28–48%, with a hardness (HR–30T) of 40–58, with a surface roughness of 0.5–1.5 microns Ra, with magnetic properties of Bm (kg) 10.0 minimum, Br (kg) 8.0 minimum, Hc (Oe) 2.5–3.8, and MU 1400 minimum, as measured with a Riken Denshi DC magnetic characteristic measuring machine, Model BHU–60.

- Bright finish tin-coated sheet with a thickness equal to or exceeding 0.0299 inch, coated to thickness of $\frac{3}{4}$ pound (0.000045 inch) and 1 pound (0.00006 inch).

- Electrolytically chromium coated steel having ultra flat shape defined as oil can maximum depth of $\frac{5}{64}$ inch (2.0 mm) and edge wave maximum of $\frac{5}{64}$ inch (2.0 mm) and no wave to penetrate more than 2.0 inches (51.0 mm) from the strip edge and coilset or curling requirements of average maximum of $\frac{5}{64}$ inch (2.0 mm) (based on six readings, three across each cut edge of a 24 inches (61 cm) long sample with no single reading exceeding $\frac{1}{32}$ inch (3.2 mm) and no more than two readings at $\frac{1}{32}$ inch (3.2 mm)) and (for 85 pound base box item only: crossbuckle maximums of 0.001 inch (0.0025 mm) average having no reading above 0.005 inch (0.127 mm)), with a camber maximum of $\frac{1}{4}$ inch (6.3 mm) per 20 feet (6.1 meters), capable of being bent 120 degrees on a 0.002 inch radius without cracking, with a chromium coating weight of metallic chromium at 100 mg/m² and chromium oxide of 10 mg/m², with a chemistry of 0.13% maximum carbon, 0.60% maximum manganese, 0.15% maximum silicon, 0.20% maximum copper, 0.04% maximum phosphorous, 0.05% maximum sulfur, and 0.20% maximum aluminum, with a surface finish of Stone Finish 7C, with a DOS–A oil at an aim level of 2 mg/square meter, with not more than 15 inclusions/foreign matter in 15 feet (4.6 meters) (with inclusions not to exceed $\frac{1}{32}$ inch (0.8 mm) in width and $\frac{3}{64}$ inch (1.2 mm) in length), with thickness/temper combinations of either 60 pound base box (0.0066 inch) double reduced CADR8 temper in widths of 25.00 inches, 27.00 inches, 27.50 inches, 28.00 inches, 28.25 inches, 28.50 inches, 29.50 inches, 29.75 inches, 30.25 inches, 31.00 inches, 32.75 inches, 33.75 inches, 35.75 inches, 36.25 inches, 39.00 inches, or 43.00 inches, or 85 pound base box (0.0094 inch) single reduced CAT4 temper in widths of 25.00 inches, 27.00 inches, 28.00 inches, 30.00 inches, 33.00 inches, 33.75 inches, 35.75 inches, 36.25 inches, or 43.00 inches, with width tolerance of $\frac{1}{8}$ inch, with a thickness tolerance of 0.0005 inch, with a maximum coil weight of 20,000 pounds (9071.0 kg), with a minimum coil weight of 18,000 pounds (8164.8 kg), with a coil inside diameter of 16 inches (40.64 cm) with a steel

core, with a coil maximum outside diameter of 59.5 inches (151.13 cm), with a maximum of one weld (identified with a paper flag) per coil, with a surface free of scratches, holes, and rust.

- Electrolytically tin coated steel having differential coating with 1.00 pound/base box equivalent on the heavy side, with varied coating equivalents in the lighter side (detailed below), with a continuous cast steel chemistry of type MR, with a surface finish of type 7B or 7C, with a surface passivation of 0.7 mg/square foot of chromium applied as a cathodic dichromate treatment, with coil form having restricted oil film weights of 0.3–0.4 grams/base box of type DOS–A oil, coil inside diameter ranging from 15.5 to 17 inches, coil outside diameter of a maximum 64 inches, with a maximum coil weight of 25,000 pounds, and with temper/coating/dimension combinations of: (1) CAT4 temper, 1.00/.050 pound/base box coating, 70 pound/base box (0.0077 inch) thickness, and 33.1875 inch ordered width; or (2) CAT5 temper, 1.00/0.50 pound/base box coating, 75 pound/base box (0.0082 inch) thickness, and 34.9375 inch or 34.1875 inch ordered width; or (3) CAT5 temper, 1.00/0.50 pound/base box coating, 107 pound/base box (0.0118 inch) thickness, and 30.5625 inch or 35.5625 inch ordered width; or (4) CADR8 temper, 1.00/0.50 pound/base box coating, 85 pound/base box (0.0093 inch) thickness, and 35.5625 inch ordered width; or (5) CADR8 temper, 1.00/0.25 pound/base box coating, 60 pound/base box (0.0066 inch) thickness, and 35.9375 inch ordered width; or (6) CADR8 temper, 1.00/0.25 pound/base box coating, 70 pound/base box (0.0077 inch) thickness, and 32.9375 inch, 33.125 inch, or 35.1875 inch ordered width.

- Electrolytically tin coated steel having differential coating with 1.00 pound/base box equivalent on the heavy side, with varied coating equivalents on the lighter side (detailed below), with a continuous cast steel chemistry of type MR, with a surface finish of type 7B or 7C, with a surface passivation of 0.5 mg/square foot of chromium applied as a cathodic dichromate treatment, with ultra flat scroll cut sheet form, with CAT5 temper with 1.00/0.10 pound/base box coating, with a lithograph logo printed in a uniform pattern on the 0.10 pound coating side with a clear protective coat, with both sides waxed to a level of 15–20 mg/216 sq. inch, with ordered dimension combinations of (1) 75 pound/base box (0.0082 inch) thickness and 34.9375 inch x 31.748 inch scroll cut dimensions; or (2) 75 pound/base box (0.0082 inch) thickness and 34.1875 inch x 29.076 inch scroll cut dimensions; or (3) 107 pound/base box (0.0118 inch) thickness and 30.5625 inch x 34.125 inch scroll cut dimension.

- Tin-free steel coated with a metallic chromium layer between 100–200 mg/m² and a chromium oxide layer between 5–30 mg/m²; chemical composition of 0.05% maximum carbon, 0.03% maximum silicon, 0.60% maximum manganese, 0.02% maximum phosphorous, and 0.02% maximum sulfur; magnetic flux density (Br) of 10 kg minimum and a coercive force (Hc) of 3.8 Oe minimum.

- Tin-free steel laminated on one or both sides of the surface with a polyester film,

consisting of two layers (an amorphous layer and an outer crystal layer), that contains no more than the indicated amounts of the following environmental hormones: 1 mg/kg BADGE (BisPhenol—A Di-glycidyl Ether), 1 mg/kg BFDGE (BisPhenol—F Di-glycidyl Ether), and 3 mg/kg BPA (BisPhenol—A).

The merchandise subject to the investigation is currently classified in the Harmonized Tariff Schedule of the United States (HTSUS), under HTSUS subheadings 7210.11.0000, 7210.12.0000, 7210.50.0020, 7210.50.0090, 7212.10.0000, and 7212.50.0000 if of non-alloy steel and under HTSUS subheadings 7225.99.0090, and 7226.99.0180 if of alloy steel. Although the subheadings are provided for convenience and customs purposes, the written description of the scope of the investigation is dispositive.

Appendix II

List of Topics Discussed in the Issues and Decision Memorandum

- I. Summary
- II. Background
- III. Period of Investigation
- IV. Scope of the Investigation
- V. Use of Facts Otherwise Available and Adverse Inference
- VI. Adjustments to Cash Deposit Rates for Export Subsidies
- VII. Affirmative Determination of Critical Circumstances
- VIII. Discussion of the Issues
 - Comment 1: Whether Commerce Properly Denied the Shougang Companies Separate Rate Status
 - Comment 2: Whether Commerce's Massive Imports Determination Was Flawed
- IX. Recommendation

[FR Doc. 2024–00320 Filed 1–9–24; 8:45 am]

BILLING CODE 3510–DS–P

DEPARTMENT OF COMMERCE

International Trade Administration

[A–570–062, C–570–063]

Cast Iron Soil Pipe Fittings From the People's Republic of China: Continuation of Antidumping Duty Order and Countervailing Duty Order

AGENCY: Enforcement and Compliance, International Trade Administration, Department of Commerce.

SUMMARY: As a result of the determinations by the U.S. Department of Commerce (Commerce) and the U.S. International Trade Commission (ITC) that revocation of the antidumping duty (AD) order and countervailing duty (CVD) order on cast iron soil pipe fittings (soil pipe fittings) from the People's Republic of China (China) would likely lead to a continuation or recurrence of dumping, countervailable subsidies, and material injury to an industry in the United States, Commerce is publishing a notice of continuation of the AD and CVD orders.

DATES: Applicable December 28, 2023.

FOR FURTHER INFORMATION CONTACT: Katherine Johnson or Henry Wolfe, AD/CVD Operations, Office VIII, Enforcement and Compliance, International Trade Administration, U.S. Department of Commerce, 1401 Constitution Avenue NW, Washington, DC 20230; telephone: (202) 482-4929 or (202) 482-0574, respectively.

SUPPLEMENTARY INFORMATION:

Background

On August 31, 2018, Commerce published in the **Federal Register** the AD order and CVD order on soil pipe fittings from China.¹ On July 3, 2023, the ITC instituted² and Commerce initiated³ the first five-year (sunset) reviews of the *Orders*, pursuant to sections 751(c) and 752 of the Tariff Act of 1930, as amended (the Act). As a result of its reviews, Commerce determined that revocation of the *Orders* would likely lead to a continuation or recurrence of dumping and countervailable subsidies, and therefore, notified the ITC of the magnitude of the margins of dumping and subsidy rates likely to prevail should the *Orders* be revoked.⁴

On December 28, 2023, the ITC published its determination, pursuant to sections 751(c) and 752(a) of the Act, that revocation of the *Orders* would likely lead to a continuation or recurrence of material injury to an industry in the United States within a reasonably foreseeable time.⁵

Scope of the Orders

The merchandise covered by these *Orders* is cast iron soil pipe fittings, finished and unfinished, regardless of industry or proprietary specifications, and regardless of size. Cast iron soil pipe fittings are nonmalleable iron castings of various designs and sizes,

¹ See *Cast Iron Soil Pipe Fittings from the People's Republic of China: Amended Final Determination of Sales at Less Than Fair Value and Antidumping Duty Order*, 83 FR 44570 (August 31, 2018); and *Cast Iron Soil Pipe Fittings from the People's Republic of China: Countervailing Duty Order*, 83 FR 44566 (August 31, 2018) (collectively, *Orders*).

² See *Cast Iron Soil Pipe Fittings from China; Institution of Five-Year Reviews*, 88 FR 42753 (July 3, 2023).

³ See *Initiation of Five-Year (Sunset) Reviews*, 88 FR 42688 (July 3, 2023).

⁴ See *Cast Iron Soil Pipe Fittings from the People's Republic of China: Final Results of the Expedited First Sunset Review of the Antidumping Duty Order*, 88 FR 76171 (November 6, 2023), and accompanying Issues and Decision Memorandum (IDM); see also *Cast Iron Soil Pipe Fittings from the People's Republic of China: Final Results of the Expedited First Sunset Review of the Countervailing Duty Order*, 88 FR 76184 (November 6, 2023), and accompanying IDM.

⁵ See *Cast Iron Soil Pipe Fittings from China*, 88 FR 89727 (December 28, 2023).

including, but not limited to, bends, tees, wyes, traps, drains, and other common or special fittings, with or without side inlets.

Cast iron soil pipe fittings are classified into two major types—hubless and hub and spigot. Hubless cast iron soil pipe fittings are manufactured without a hub, generally in compliance with Cast Iron Soil Pipe Institute (CISPI) specification 301 and/or American Society for Testing and Materials (ASTM) specification A888. Hub and spigot pipe fittings have hubs into which the spigot (plain end) of the pipe or fitting is inserted. Cast iron soil pipe fittings are generally distinguished from other types of nonmalleable cast iron fittings by the manner in which they are connected to cast iron soil pipe and other fittings.

Excluded from the scope are all drain bodies. Drain bodies are normally classified in subheading 7326.90.86.88 of the Harmonized Tariff Schedule of the United States (HTSUS).

The subject imports are normally classified in subheading 7307.11.0045 of the HTSUS: Cast fittings of nonmalleable cast iron for cast iron soil pipe. They may also be entered under HTSUS 7324.29.0000 and 7307.92.3010. The HTSUS subheadings and specifications are provided for convenience and customs purposes only; the written description of the scope of these *Orders* is dispositive.

Continuation of the Orders

As a result of the determinations by Commerce and the ITC that revocation of the *Orders* would likely lead to a continuation or recurrence of dumping, countervailable subsidies, and material injury to an industry in the United States, pursuant to sections 751(c) and 751(d)(2) of the Act, Commerce hereby orders the continuation of the *Orders*. U.S. Customs and Border Protection will continue to collect AD and CVD cash deposits at the rates in effect at the time of entry for all imports of subject merchandise.

The effective date of the continuation of the *Orders* will be December 28, 2023.⁶ Pursuant to section 751(c)(2) of the Act, Commerce intends to initiate the next five-year reviews of these *Orders* not later than 30 days prior to the fifth anniversary of the effective date of continuation.

Administrative Protective Order (APO)

This notice also serves as a final reminder to parties subject to an APO of their responsibility concerning the return or destruction of proprietary

information disclosed under APO in accordance with 19 CFR 351.305(a)(3), which continues to govern business proprietary information in this segment of the proceeding. Timely written notification of the return or destruction of APO materials, or conversion to judicial protective order, is hereby requested. Failure to comply with the regulations and terms of an APO is a violation which is subject to sanction.

Notification to Interested Parties

These five-year (sunset) reviews and this notice are in accordance with sections 751(c) and 751(d)(2) of the Act and published in accordance with 777(i) the Act, and 19 CFR 351.218(f)(4).

Dated: January 4, 2024.

Abdelali Elouaradia,

Deputy Assistant Secretary for Enforcement and Compliance.

[FR Doc. 2024-00329 Filed 1-9-24; 8:45 am]

BILLING CODE 3510-DS-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-122-869]

Tin Mill Products From Canada: Final Affirmative Determination of Sales at Less Than Fair Value and Final Negative Determination of Critical Circumstances

AGENCY: Enforcement and Compliance, International Trade Administration, Department of Commerce.

SUMMARY: The U.S. Department of Commerce (Commerce) determines that imports of tin mill products from Canada are being, or are likely to be, sold in the United States at less than fair value (LTFV). The period of investigation January 1, 2022, through December 31, 2022.

DATES: Applicable January 10, 2024.

FOR FURTHER INFORMATION CONTACT: Yang Jin Chun, AD/CVD Operations, Office VI, Enforcement and Compliance, International Trade Administration, U.S. Department of Commerce, 1401 Constitution Avenue NW, Washington, DC 20230; telephone: (202) 482-5760.

SUPPLEMENTARY INFORMATION:

Background

On August 22, 2023, Commerce published in the **Federal Register** its preliminary affirmative determination in the LTFV investigation of tin mill products from Canada, in which it also postponed the final determination until January 4, 2024.¹ We invited interested

¹ See *Tin Mill Products from Canada: Preliminary Affirmative Determination of Sales at Less Than*

⁶ *Id.*